800 Series Downdraft - HDD80051UC





HDD80051UC Stainless Steel

Sleek, built-in, and retracts out of sight. Bosch 30" Downdraft's flexible design seamlessly integrates into your kitchen

| Features & Benefits |
|--|
| Beautifully designed to preserve clean sight lines when not in use |
| Sleek front panel filter design acts as a guard against splatters |
| 6 exhaust connections possible (transition sold separately) |
| Recirculation kit for sale for use in non ducted applications* |

| General Properties | | | | | | | | |
|--|---|--|--|--|--|--|--|--|
| Operating mode | Convertible: ducted / recirculating | | | | | | | |
| Maximum CFM | Blower sold separately | | | | | | | |
| Number of speed settings | 3-stage | | | | | | | |
| Motor location | External | | | | | | | |
| Damper included | No | | | | | | | |
| Grease filter material | Aluminum | | | | | | | |
| Grease filter type | Multilayer cassette | | | | | | | |
| Duct direction | Front, Left, Right, Rear, Down | | | | | | | |
| Optional blower required | Yes (600 CFM options sold separately) | | | | | | | |
| Technical Details | | | | | | | | |
| Volts (V) | 120 V | | | | | | | |
| Frequency (Hz) | 60 Hz | | | | | | | |
| Plug type | 120V-3 prong | | | | | | | |
| Power cord length (in.) | 30" | | | | | | | |
| Dimensions & Weight | | | | | | | | |
| Overall appliance dimensions (width of canopy included) (HxWxD) (in.) | 29 3/8 " x 31" x 2 3/4 " | | | | | | | |
| Height of the rise (in.) | 12" | | | | | | | |
| Diameter of air duct (in.) internal | 8" | | | | | | | |
| Diameter of air duct (in.) external | 6" or 8" | | | | | | | |
| Net weight (lbs) | 37 lbs | | | | | | | |
| Accessories – Required | | | | | | | | |
| Blower (sold separately) | | | | | | | | |

| | 8 Diamara | | | | | | |
|--|------------|--|--|--|--|--|--|
| Accessories – Transitions | | | | | | | |
| 6" side / rear / downward transition | HDDSTRAN6 | | | | | | |
| 8" side / rear / downward transition | HDDSTRAN8 | | | | | | |
| NOTE: HDDSTRAN6 or HDDSTRAN8 required for side, rear or downward exhaust applications with inline and remote blowers. | | | | | | | |
| 6" round front plate | HDDFTRAN6 | | | | | | |
| 8" round front plate | HDDFTRAN8 | | | | | | |
| NOTE: HDDFTRAN6 or HDDFTRAN8 required for front exhaust applications with inline and remote blowers. | | | | | | | |
| Transition for rectangular duct | HDDSTRAN2 | | | | | | |
| 2' rectangular duct | HDD2RECTD | | | | | | |
| NOTE: HDDSTRAN2 needed to attach HDD2RECTD to downdraft. For use with installation of inline or remote blower applications. | | | | | | | |
| 600 CFM flexible blower | DHG602DUC | | | | | | |
| 600 CFM inline blower | DHI1FZUC | | | | | | |
| 600 CFM remote blower | DHR1FZUC | | | | | | |
| Accessories – Optional | | | | | | | |
| Recirculation kit (compatible with electric and induction cooktops only) | HDDREC5UC | | | | | | |
| Charcoal filter replacement for recirculation kit | HDDFILTUC | | | | | | |
| 30" gas cooktop seal kit for downdraft (required for installation with gas cooktops) | HDDORSP | | | | | | |
| Trim kit for 30" FlameSelect® gas cooktops | HDDTRIM30S | | | | | | |



*Recirculation kit is not compatible with gas cooktop installations with downdraft

Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904


800 Series Downdraft - HDD80051UC




HVI Performance Values (CFM & Sones)

| Downdraft HDD80051UC with Blower DHG602DUC | | | | | | | | | | | |
|--|-----------|--------------------------------------|--------------------|------------------|---------------|------------------|---------------|------------------|---------------|------------------|--|
| | | | Pressure (in. H2O) | | Power (W) | | CFM | | Sones | | |
| Exhaust | Duct Size | Required Accessories | High Speed | Working Speed | High Speed | Working Speed | High Speed | Working Speed | High Speed | Working Speed | |
| Front | 8" Round | None | 0.1 | 0.018 | 285 | 68.5 | 380 | 160 | 12.0 | 2.0 | |
| Left | 8" Round | Optional Adapter Model: HDDSTRAN8 | 0.1 | 0.016 | 279 | 67.0 | 360 | 150 | 11.0 | 2.5 | |
| Right | 8" Round | | 0.1 | 0.017 | 288 | 65.7 | 350 | 140 | 11.0 | 1.4 | |
| Rear | 8" Round | | 0.1 | 0.018 | 279 | 66.9 | 360 | 150 | 10.0 | 1.5 | |
| Bottom | 8" Round | | 0.1 | 0.018 | 286 | 66.0 | 370 | 150 | 11.0 | 1.5 | |
| Front | 8" Round | None | 0.25 | _ | _ | _ | 360 | _ | - | _ | |
| Left | 8" Round | Optional Adapter Model: HDDSTRAN8 | 0.25 | _ | _ | _ | 340 | _ | - | _ | |
| Right | 8" Round | | 0.25 | _ | _ | _ | 330 | _ | - | _ | |
| Rear | 8" Round | | 0.25 | _ | _ | _ | 340 | _ | _ | _ | |
| Bottom | 8" Round | | 0.25 | | _ | _ | 350 | _ | _ | _ | |

Installation Details




CLEARANCES



800 Series Downdraft - HDD80051UC



Installation Details – Cutouts




Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

800 Series Downdraft - HDD80051UC



Accessories – Transitions




Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

800 Series Downdraft - HDD80051UC



Accessories – Transitions




Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

800 Series Downdraft - HDD80051UC



Accessories - 600 CFM Blowers




Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

800 Series Downdraft - HDD80051UC



Accessories – Optional




Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

800 Series Downdraft - HDD80051UC




Flexible Blower Installation – Front Exhaust Example



Application

- Flexible blower attached can rotate for left, right or downward discharge
- Front downward application with flexible blower
- Requires space under floor line for ductwork*
- Can be used with optional Recirculation Kit, sold separately
- · Elbow, ductwork, blower support structure frame not included

Required Blower



DHG602DUC

600 CFM Flexible Integral Blower


600 CFM flexible blower can mount to downdraft or be used as an inline blower, and can be rotated to exhaust downward or to sides

*) measurements in inches and (mm)

Optional Accessories

HDDREC5UC

Recirculation Kit for Downdraft When ducting to the exterior is not feasible, downdraft recirculation kit allows filtered air to reenter the kitchen while cooking



Measurements in inches and (mm)

HDDFILTUC

Charcoal Filter Replacement for Recirculation Kit for Downdraft

Maintain performance of Bosch downdraft recirculation kit with timely replacement of charcoal filter to capture and filter odors

HDD0RSP

30" Gas Cooktop Seal Kit for Downdraft30" gas cooktop seal kit required for installation with 30" gas cooktops



*For only front downward ducting applications, electrical panel must be remotely mounted. Electrical panel can still be remotely mounted in other exhaust configurations if desired. Electrical panel interconnect cable length is 5-ft. long.


Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904


800 Series Downdraft - HDD80051UC



Flexible Blower Installation – Front Exhaust with Flexible Blower Used as an **Inline Option Example**




Required Accessories



Application

- · Side exhaust with flexible blower used as inline option if ducting is more convenient with this configuration
- Requires at least 18" of clearance to fit the blower and transition
- Blower must be accessible for maintenance
- · Elbow, ductwork, blower support structure frame not included

Required Blower



DHG602DUC

600 CFM Flexible Integral Blower

600 CFM flexible blower can mount to downdraft or be used as an inline blower, and can be rotated to exhaust downward or to sides

measurements in inches and (mm)

Optional Accessories

HDDORSP

30" Gas Cooktop Seal Kit for Downdraft 30" gas cooktop seal kit required for installation with 30" gas cooktops



NOTE: Some applications may require deeper cabinets. Side and rear exhaust require at least 18" of clearance to fit the blower and / or ductwork. Refer to installation instructions.


Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST). Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904


800 Series Downdraft - HDD80051UC



Flexible Blower Installation – Side Exhaust Example



Left Side Exhaust



Right Side Exhaust


Required Accessories

HDDSTRAN8

8" Side / Rear / Downward Transition for Downdraft

8" Round transition enable ducting to be at sides, rear or below downdraft for flexible configurations to maximize your kitchen design

NOTE: HDDSTRAN8 side / rear / downward transition required for side, rear or downward exhaust applications with inline and remote blowers.




measurements in inches (mm)

Application

- · Side exhaust option if ducting is more convenient with this configuration
- Requires at least 18" of clearance to fit the blower and transition
- · Can be used with optional Recirculation Kit, sold separately
- · Elbow, ductwork, blower support structure frame not included

Required Blower



DHG602DUC

600 CFM Flexible Integral Blower

600 CFM flexible blower can mount to downdraft or be used as an inline blower, and can be rotated to exhaust downward or to sides


measurements in inches and (mm)

Optional Accessories

HDDREC5UC

Recirculation Kit for Downdraft

When ducting to the exterior is not feasible, downdraft recirculation kit allows filtered air to reenter the kitchen while cooking



HDDFILTUC

Charcoal Filter Replacement for Recirculation Kit for Downdraft

Maintain performance of Bosch downdraft recirculation kit with timely replacement of charcoal filter to capture and filter odors

HDD0RSP

30" Gas Cooktop Seal Kit for Downdraft

30" gas cooktop seal kit required for installation with 30" gas cooktops





NOTE: Some applications may require deeper cabinets. Side and rear exhaust require at least 18" of clearance to fit the blower and / or ductwork. Refer to installation instructions.


Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

800 Series Downdraft - HDD80051UC



Flexible Blower Installation - Side Exhaust with Slim 2' Rectangular Duct Example




Required Accessories

HDD2RECTD

2' Rectangular Duct Downdraft

2' Rectangular duct can be used as extension to exhaust through a cabinet or wall while maximizing cabinet storage space



measurements in inches (mm)

HDDSTRAN2


Transition for Rectangular Duct for Downdraft Rectangular duct transition required to connect 2' rectangular duct to downdraft

HDDSTRAN8


8" Side / Rear / Downward Transition for Downdraft

8" Round transition enable ducting to be at sides, rear or below downdraft for flexible configurations to maximize your kitchen design

NOTE: HDDSTRAN8 side / rear / downward transition required for side, rear or downward exhaust applications with inline and remote blowers.



(48 mm) measurements in inches (mm)




measurements in inches (mm)

Application

- · Side exhaust option if ducting is more convenient with this configuration
- A slim 2' rectangular duct is available to place flexible blower in areas such as unused corner in island or peninsula applications
- · Can be used with optional Recirculation Kit, sold separately
- Elbow, ductwork, blower support structure frame not included

Required Blower



DHG602DUC

600 CFM Flexible Integral Blower


600 CFM flexible blower can mount to downdraft or be used as an inline blower, and can be rotated to exhaust downward or to sides

measurements in inches and (mm)

Optional Accessories

HDDREC5UC

Recirculation Kit for Downdraft When ducting to the exterior is not feasible, downdraft recirculation kit allows filtered air to reenter the kitchen while cooking



HDDFILTUC

Charcoal Filter Replacement for Recirculation Kit for Downdraft

Maintain performance of Bosch downdraft recirculation kit with timely replacement of charcoal filter to capture and filter odors

HDD0RSP

30" Gas Cooktop Seal Kit for Downdraft 30" gas cooktop seal kit required for installation with 30" gas cooktops





NOTE: Some applications may require deeper cabinets. Side and rear exhaust require at least 18" of clearance to fit the blower and / or ductwork. Refer to installation instructions.


Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST). Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

800 Series Downdraft - HDD80051UC



Flexible Blower Installation – Rear Exhaust Example




Required Accessories

HDDSTRAN8

8" Side / Rear / Downward Transition for Downdraft

8" Round transition enable ducting to be at sides, rear or below downdraft for flexible configurations to maximize your kitchen design

NOTE: HDDSTRAN8 side / rear / downward transition required for side, rear or downward exhaust applications with inline and remote blowers.




measurements in inches (mm)

Application

- · Rear exhaust option is possible if ducting is more convenient with this configuration
- Requires at least 18" of clearance to fit the blower and transition
- Blower must be accessible for maintenance
- · Can be used with optional Recirculation Kit, sold separately
- · Elbow, ductwork, blower support structure frame not included

Required Blower



DHG602DUC

600 CFM Flexible Integral Blower


600 CFM flexible blower can mount to downdraft or be used as an inline blower, and can be rotated to exhaust downward or to sides

measurements in inches and (mm)

Optional Accessories

HDDREC5UC

Recirculation Kit for Downdraft When ducting to the exterior is not feasible, downdraft recirculation kit allows filtered air to reenter the kitchen while cooking



HDDFILTUC

Charcoal Filter Replacement for Recirculation Kit for Downdraft

Maintain performance of Bosch downdraft recirculation kit with timely replacement of charcoal filter to capture and filter odors

HDD0RSP

with 30" gas cooktops

30" Gas Cooktop Seal Kit for Downdraft 30" gas cooktop seal kit required for installation



NOTE: Some applications may require deeper cabinets. Side and rear exhaust require at least 18" of clearance to fit the blower and / or ductwork. Refer to installation instructions.


Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST). Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

800 Series Downdraft - HDD80051UC



Flexible Blower Installation – Downward Exhaust Example




Required Accessories

HDDSTRAN8

8" Side / Rear / Downward Transition for Downdraft

8" Round transition enable ducting to be at sides, rear or below downdraft for flexible configurations to maximize your kitchen design

NOTE: HDDSTRAN8 side / rear / downward transition required for side, rear or downward exhaust applications with inline and remote blowers.




measurements in inches (mm)

Application

- · Downward exhaust option if ducting is more convenient with this configuration
- Requires at least 18" of clearance to fit the blower and transition
- · Can be used with optional Recirculation Kit, sold separately
- Elbow, ductwork, blower support structure frame not included
- · Blower must be accessible for maintenance
- · Can also be installed with inline and remote blowers

Required Blower



DHG602DUC


600 CFM Flexible Integral Blower 600 CFM flexible blower can mount to downdraft or be used as an inline blower, and can be rotated to exhaust downward or to sides

measurements in inches and (mm)

Optional Accessories

HDDREC5UC

Recirculation Kit for Downdraft When ducting to the exterior is not feasible, downdraft recirculation kit allows filtered air to reenter the kitchen while cooking



HDDFILTUC

Charcoal Filter Replacement for Recirculation Kit for Downdraft

Maintain performance of Bosch downdraft recirculation kit with timely replacement of charcoal filter to capture and filter odors

HDD0RSP

30" Gas Cooktop Seal Kit for Downdraft 30" gas cooktop seal kit required for installation with 30" gas cooktops






Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

800 Series Downdraft - HDD80051UC



Flexible Blower Installation – Recirculation Example




Required Accessories

HDDREC5UC

Recirculation Kit for Downdraft When ducting to the exterior is not feasible, downdraft recirculation kit allows filtered air to reenter the kitchen while cooking

> 173/4 Measurements in inches and (mm) (450)



EXHAUST THROUGH CABINET BACK Measurements in inches (mm). 14 1/2" (368) 15" (380)1/2" (89) x 14 1/4" (362) DECORATIVE EXHAUST OPENING GRILLE

132/4

(342)

dia. 7³/4"

(dia 200)

Å3/₄

16

(406)

. 3³/4"

15

(380)


16¹/8">

(408)

Application

- Allows for non-ducted downdraft installation by eliminating the need to exhaust to the exterior of the home
- Mount to toe kick or base of a cabinet and attach directly to flexible blower
- Recirculation module and metal grill vent plate placement can be rotated for flexible exhaust placement
- Elbow, ductwork, blower support structure frame not included

Required Blower



DHG602DUC

600 CFM Flexible Integral Blower

600 CFM flexible blower can mount to downdraft or be used as an inline blower, and can be rotated to exhaust downward or to sides

measurements in inches and (mm)

Optional Accessories

HDDFILTUC

Charcoal Filter Replacement for Recirculation Kit for Downdraft

Maintain performance of Bosch downdraft recirculation kit with timely replacement of charcoal filter to capture and filter odors

HDD0RSP

30" Gas Cooktop Seal Kit for Downdraft 30" gas cooktop seal kit required for installation with 30" gas cooktops





Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904