

MEDS302WS

30-INCH DOUBLE COMBINATION BUILT-IN OVEN

WITH STEAM CONVECTION

MASTERPIECE® SERIES



FEATURES & BENEFITS

- Specially crafted gray glass on stainless steel for a luxurious look and finish
- Designed for flexibility—standard or flush installation into kitchen cabinets
- Steam and Convection Cooking provides unrivaled taste and quality—food stays moist on the inside and is perfect on the outside
- Steam and Convection Oven offers passionate cooks more cooking solutions - Broil, Steam, True Convection, Steam and Convection
- Large commercial style rotisserie with 12 pound capacity

ACCESSORIES (INCLUDED)

Upper Cavity: 3 Telescopic Racks, Multi-point Meat Probe, Broil Pan, 1 Large Pan, 1 Small Pan, 1 Small Perforated Pan; Lower Cavity: 3 Telescopic Racks, Multi-point Meat Probe, Max Broil Pan, Rotisserie

WARRANTY

Limited Warranty Parts and Labor	2 Year
----------------------------------	--------

GENERAL PROPERTIES

Heating Modes – Upper Cavity
 (17) Bake, Broil, Roast, Convection Bake, Convection Broil, Convection Roast, Steam Convection, Defrost, Proof, Warm, Pizza, True Convection, Dehydrate, Speed Convection, Slow Roast, Steam, Reheat, Steam Auto Programs

Heating Modes – Lower Cavity
 (16) Bake, Broil, Max Broil, Roast, Convection Bake, Convection Broil, Max Convection Broil, Convection Roast, Proof, Warm, Pizza, True Convection, Dehydrate, Speed Convection, Slow Roast, Rotisserie

Sabbath	Yes	
Cleaning Type	Upper Cavity	Easy Clean, Ecolytic Clean
	Lower Cavity	Easy Clean and Self Clean
Telescopic Rack(s)	6	
Illumination Type	Upper Cavity	LED
	Lower Cavity	Halogen
Interior Lights	Upper Cavity	3 – 1 Top, 2-Sides
	Lower Cavity	2 – Sides with 2 Bulbs Each
Home Connect® (Wi-Fi Enabled)	Yes, Upper & Lower	

OVEN PERFORMANCE

Bake / Broil Element	Upper Cavity	1,420 W / 3,050 W
	Lower Cavity	2,400 / 1,000 / 3,800 W
Convection Element	Upper Cavity	2,300 W
	Lower Cavity	2,000 W

TECHNICAL DETAILS

Watts	9,200 W	
Circuit Breaker	40 A	
Volts; Frequency	240 / 208 V; 60 Hz	
Plug Type	Fixed Connection, No Plug	
Conduit	60" 4-Wire	
Energy Source	Electric	

DIMENSIONS & WEIGHT

Overall Appliance Dimensions (HxWxD)	48 7/8" x 29 3/4" x 24 1/2"	
Trim Overlaps (Top – Sides – Bottom)	3/4" to 1 1/2" – 9/16" – 0"	
Required Cutout Size (HxWxD) – Standard	47 3/8"- 48 1/8" x 28 1/2" x 23 1/2"	
Required Cutout Size (HxWxD) – Flush	49" x 30" x 24 1/2"	
Steam Convection Oven Capacity	2.8 cu. ft.	
Oven Capacity	4.5 cu. ft.	
Overall Oven Interior Dimensions (HxWxD)	Upper Cavity	14 1/2" x 18 7/8" x 17 3/8"
	Lower Cavity	17 3/4" x 24" x 17 7/8"
Usable Oven Interior Dimensions (HxWxD)	Upper Cavity	11 1/2" x 15 1/2" x 15 5/8"
	Lower Cavity	13 1/2" x 21 5/8" x 16 1/4"
Net Weight	333 lbs	

MEDS302WS

30-INCH DOUBLE COMBINATION BUILT-IN OVEN WITH STEAM CONVECTION

MASTERPIECE® SERIES



30-INCH DOUBLE COMBINATION OVEN

Combination Oven with Steam and Convection Oven
Wall Mount Installation

measurements in inches (mm)

Door Handle Depth*
Masterpiece Series Handl

*Protrusion of handle from door skin

Combination Oven with Steam and Convection Oven
Wall Mount Installation

measurements in inches (mm)

* Junction box may be installed above, beneath, right or left of the unit within reach of the power cord.

Combination Oven with Steam and Convection Oven
Flush Mount Installation

Top View Bottom Hinge Door

measurements in inches (mm)

Side View-Combination Oven with Steam and Convection Oven

measurements in inches (mm)



MEDS302WS

30-INCH DOUBLE COMBINATION BUILT-IN OVEN WITH STEAM CONVECTION

MASTERPIECE® SERIES



INSTALLATION DETAILS



These warranties give you specific legal rights and you may have other rights that vary from state to state. Limited warranty from date of delivery. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.