

PO302W

30-INCH DOUBLE BUILT-IN OVEN

PROFESSIONAL SERIES



Home Connect

FEATURES & BENEFITS

- Specially crafted gray glass on stainless steel for a luxurious look and finish
- Designed for flexibility—standard or flush installation into kitchen cabinets
- SoftClose® door ensures ultra smooth closing of the oven door
- Full Access® telescopic rack
- Fast 2-hour self clean mode
- Fast preheat (around 7 minutes)

ACCESSORIES (INCLUDED)

Upper Cavity: 1 Telescopic and 2 Standard Oven Racks, Meat Probe, Broil Pan; Lower Cavity: 1 Telescopic and 2 Standard Oven Racks

GENERAL PROPERTIES

Heating Modes – Upper Cavity

(13) Bake, Broil, Roast, Convection Bake, Convection Broil, Convection Roast, Proof, Warm, Pizza, True Convection, Dehydrate, Speed Convection, Slow Roast

Heating Modes – Lower Cavity

(13) Bake, Broil, Roast, Convection Bake, Convection Broil, Convection Roast, Proof, Warm, Pizza, True Convection, Dehydrate, Speed Convection, Slow Roast

| | | |
|-------------------------------|------------------------------|--------------------------------------------------|
| Sabbath | | Yes |
| Cleaning Type | Upper Cavity Lower Cavity | Easy Clean, Self Clean Easy Clean, Self Clean |
| Telescopic Rack(s) | | 2 |
| Illumination Type | Upper Cavity Lower Cavity | Halogen Halogen |
| Interior Lights | Upper Cavity Lower Cavity | 2 2 |
| Home Connect® (Wi-Fi Enabled) | | Yes |

OVEN PERFORMANCE

| | | |
|----------------------|------------------------------|------------------------------------|
| Bake / Broil Element | Upper Cavity Lower Cavity | 2,400 / 3,800 W 2,400 / 3,800 W |
| Convection Element | Upper Cavity Lower Cavity | 2,000 W 2,000 W |

TECHNICAL DETAILS

| | | |
|-------------------|--|---------------------------|
| Watts | | 9,200 W |
| Circuit Breaker | | 40 A |
| Volts | | 240 / 208 V |
| Frequency | | 60 Hz |
| Power Cord Length | | 60" |
| Plug Type | | Fixed Connection, No Plug |
| Conduit | | 60" 4-Wire |
| Energy Source | | Electric |

DIMENSIONS & WEIGHT

| | | |
|------------------------------------------|------------------------------|-----------------------------------|
| Overall Appliance Dimensions (HxWxD) | | 52 1/16" x 29 3/4" x 24 1/2" |
| Trim Overlaps (Top – Sides – Bottom) | | 3/8" to 2" – 9/16" – 0" |
| Required Cutout Size (HxWxD) – Standard | | 50" – 51 1/2" x 28 1/2" x 23 1/2" |
| Required Cutout Size (HxWxD) – Flush | | 52 3/16" x 30" x 24 1/2" |
| Oven Cavity Size | Upper Cavity Lower Cavity | 4.5 cu. ft. 4.5 cu. ft. |
| Overall Oven Interior Dimensions (HxWxD) | | 17 3/4" x 24" x 17 7/8" |
| Usable Oven Interior Dimensions (HxWxD) | | 13 1/2" x 21 5/8" x 16 1/4" |
| Net Weight | | 323 lbs |

WARRANTY

| | | |
|----------------------------------|--|--------|
| Limited Warranty Parts and Labor | | 2 Year |
|----------------------------------|--|--------|

PO302W

30-INCH DOUBLE BUILT-IN OVEN

PROFESSIONAL SERIES



30-INCH DOUBLE OVEN

Double Oven Wall Mount Installation
Double Oven Bottom Hinge

50" (1270 mm)
28⁷/₁₆" (722 mm)
29³/₄" (756 mm)
49³/₄" (1264 mm)
52¹/₁₆" (1324 mm)
23¹/₂" (597 mm)
24¹/₂" (622 mm)
22³/₈" (568 mm)

measurements in inches (mm)

Door Handle Depth*
Professional Series Handle

2⁵/₈" (67 mm)

*Protrusion of handle from door skin

Double Oven Wall Mount Installation

28¹/₂" (724 mm)
23¹/₂" (597 mm)
50"-51¹/₂" (1270-1308 mm)
4³/₄"-14⁷/₈" (121-378 mm)

* For double ovens installed into a wall cabinet, the junction box may be located above or beneath the unit within reach of the power cord.

**For oven installation in a wall cabinet, the control panel overlap is a min. ³/₈" (10 mm) to max. 1¹/₄" (25 mm).

measurements in inches (mm)

Double Oven Flush Mount Installation
Top View Bottom Hinge Door

3/4" (19 mm) reveal cleats
3/4" (19 mm) reveal cleats
24¹/₂" (622 mm) flush inset depth
1" (25 mm)
28¹/₂" (724 mm)
30" (762 mm)

measurements in inches (mm)

Double Oven Flush Mount Installation
Side View Right Hinge, Left Hinge and Bottom Hinge

1" (25 mm)
reveal cleats
52³/₁₆" (1326 mm) flush cut-out height
24¹/₂" (622 mm)

measurements in inches (mm)



PO302W

30-INCH DOUBLE BUILT-IN OVEN

PROFESSIONAL SERIES



INSTALLATION DETAILS



These warranties give you specific legal rights and you may have other rights that vary from state to state. Limited warranty from date of delivery. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.