



AR 403 722
Metal housing
562 CFM
Air extraction

Inline blower 400 and 200 series AR 403

- Powerful inline blower to combine with motorless appliances AL400, VL200, VL414
- Efficient BLDC technology
- Compact and space-saving installation in a 4" (10 cm) high toe-kick

Output

3 performance output levels and intensive mode:
Sound power and sound pressure depending on built-in situation.
Air extraction: 562 CFM.
Power levels depend on the downdraft appliances.

Features

3 electronically controlled power levels and 1 intensive mode.
Fan technology with highly efficient, brushless DC motor (BLDC).
Steel housing, zinc-plated.
Pipe connection pieces on intake side:
1 x 6" DN 150 round.
Pipe connection pieces on output side:
1 x DN 150 flat duct.
Retaining bracket for installation on the ceiling or side of enclosed cabinet.

Planning notes

Inline blower in combination with AL400, VL200, VL414.
Connection to the respective appliances via network cable.
Installation in the toe-kick with cut-out for the air ducting in the cabinet base.
Connection of AL 400 with an air collector box (AD 704 048/049).

Connection

Total rating 170 W.
Total amps : 2 A
120 V / 60 Hz.
Includes a 60" (1.5 m) electrical cable.
Hardwire required.
78" (2 m) network cable included to connect with VL or AL downdraft. .

