

Color Variants VG295250CA Width 36" (90 cm) Natural gas.

**Optional accessories** WP400001 Wok pan made of multiple-layer material

VG295250CA 200 series gas cooktop Width 36" (90 cm) Natural gas. Up to 59,700 BTU (17.5 kW) on 5 burners

Control panel for comfortable and secure operation Mechanical power level regulation for 9 power levels, with exact setting and reproduction of flame size Multi-ring burner of solid, heat-resistant brass as used in professional kitchen Solid smooth-surface cast-iron pan support Up to 59,700 BTU (17.5 kW) on 5 burners

## Cooking zones

1 multi-ring wok burner 1,000 - 18,800 BTU (300 W – 5500 W), suitable for pots up to max. ø 12 5/8". 2 two-ring high output burners 600 -13,600 BTU (170 W - 4000 W), suitable for pots up to max. ø 11". 2 two-ring standard burners 600 - 6,800 BTU (170 W - 2000 W), suitable for pots up to max. ø 9 1/2".

#### Operation

Control knobs with illuminated ring. Integrated control panel. One-handed operation. Electric ignition.

### Features

Three-part cast iron pan support with flat, continuous pot surface. Brass burner rings.

### Safety

Thermoelectric safety pilot. Residual heat indicator. Operation indicator.

# Planning notes

No intermediate shelf required. Appliance can be snapped into the countertop from above. The rear panel must consist of a nonflammable material. Wall trims must be resistant to heat. Installation in a 36" (90 cm) wide base cabinet is required. Above countertop minimum clearance of at least 11 13/16" from adjacent heat-sensitive furniture or contact surfaces must be observed or thermal insulation must be installed. Minimum distance between gas cooktop(s) with more than 37,533 BTU (11kW) and ventilation hood must be 30" (76cm). Appliance weight: approx. 29 kg.

## Rating

Total rating: 58,000 BTU (17.5 KW). Total Amps: 1 A. 120 V / 60 Hz Connecting cable 55" with plug.

### Product Features

Product name / series name gas hob w integrated controls Construction type Built-in Energy source Gas Total number of cooktop burners Required cutout size (HxWxD) (mm) 106 x 885 x 492 Width of the appliance 914 Dimensions 106 x 914 x 510 Product packaging dimensions (HxWxD) (mm) 290 x 700 x 1010 Net weight (kg) 28.879 Gross weight (kg) 31.2 Residual heat indicator Location of control panel Basic surface material brushed stainless steel Color of surface Stainless steel Color of frame


Stainless steel Approval certificates CSA, CSA, CSA Power cord length (cm) 150

Consumption and connection features Watts (W) 10 Gas connection rating (W) 17500

Current (A) 10 Volts (V) 110-120 Frequency (Hz) 60

2020-10-10 Page 1





Gas connection

