QUICK REFERENCE GUIDE > CDV3-365-L

# Gas Cooktop, 36", LPG

Series 7 | Professional

Stainless Steel | LPG



A powerful high-heat five burner with precision control and performance. Pair with any other appliance in our Professional range.

- Your burners can deliver anything from a high 20,000 BTU heat per burner for fast boiling, to a gentle flame for simmering
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- Designed to match Professional style appliances
- Made from quality materials and real stainless steel

## **DIMENSIONS**

Height	5 1/2'
Width	36′
Depth	21′

## **FEATURES & BENEFITS**

## COOKTOP POWER

Sealed Dual Flow Burners™ deliver cooktop power up to 20,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

#### PRECISE CONTROL

From the highest to the lowest temperatures you get total control. A precise full surface simmer is delivered across all burners.

#### COOKING FLEXIBILITY

The self-locating grates focus the flame on the base of each pan, where it is most required. They are designed for easy and safe sliding of pans across the cooktop surface. For cooking variety, a wok ring accessory is also available.

#### **EASY TO CLEAN**

These cooktops are easy to clean with a commercial-style stainless steel finish, sealed burners and a single sheet cooking surface.

## COMPLEMENTARY DESIGN

Built to last with distinctive, bold styling, this cooktop is designed to match the Fisher & Paykel Professional style family of appliances.

## **SPECIFICATIONS**

## **Burner ratings**

Max burner power Yes

Power back left	12,000 BTU
Power back right	12,000 BTU
Power front centre	20,000 BTU
Power front left	12,000 BTU
Power front right	12,000 BTU
Total cooktop power	68,000 BTU

#### Controls

Metal dials

#### **Gas Requirements**

Fitting and pipe ½ NPT, min. %" 🛚 flex line Supply Pressure (LPG) 11" to 14" W.C

#### Performance

Sealed Dual Flow Burners™ 5

Sealed cooking surface •

Simmer on all burners 140°F

## Power requirements

Amperage 15A
Supply frequency 60Hz
Supply voltage 120V

## **Product dimensions**

 Depth
 21"

 Height
 5 1/2"

 Width
 36"

## Recommended Back Guards Ventilation

QUICK REFERENCE GUIDE > CDV3-365-L

Downdraft	HD36
Minimum CFM	600 BTU
Pro hood	HCB36-12 N / HCB36-6 N
Traditional hood	ES36
Safety	
ADA compliant	•
Warranty	
Parts and labor	2 years
SKU	82021

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

## Other product downloads available at fisherpaykel.com



User Guide



Service & Warranty



Installation Guide



## A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

**T** 1.888.936.7872 **W**www.fisherpaykel.com