Gas Rangetop, 48", LPG

Series 9 | Professional

Stainless Steel | LPG



Eight burners for when you need maximum performance and cooktop space - great for those who love to cook for a crowd.

- Your burners can deliver anything from very high 19,000 BTU heat for seriously fast boiling, to the most gentle flame for simmering
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- Designed to match Professional style appliances
- Made from quality materials and real stainless steel

DIMENSIONS

Height	8 5/16″
Width	47 7/8"
Depth	28"

FEATURES & BENEFITS

COOKTOP POWER

Sealed Dual Flow Burners[™] deliver rangetop power up to 19,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

PRECISE CONTROL

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

PRECISE CONTROL

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

COOKING FLEXIBILITY

The continuous surface grates are designed for pots and pans to move safely across the rangetop. The deep-platform style grates provide full coverage so heat goes directly onto the pot, for a faster boil.

EASY TO CLEAN

These rangetops are easy to clean with sealed burners and a continuous, porcelain basepan.

INFORMATION AT A GLANCE

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

DESIGN QUALITY

This rangetop is built to last with craftsmanship in every detail, featuring real stainless steel, cast-iron grates, and titanium coated dials.

Fitting and pipe½ NPT, min. %" ∅ flex lineSupply Pressure (LPG)11" to 14" W.C

Performance

Star K Certification

Gas Requirements

Titanium coated, illuminated

Sealed Dual Flow Burners™	8
Sealed cooking surface	•

SPECIFICATIONS

Burner ratings	
Max burner power	Ye
Power back centre	13,000 BTU
Power back centre (2)	13,000 BTU
Power back left	13,000 BTU
Power back right	13,000 BTU
Power front centre	15,000 BTU
Power front centre (2)	15,000 BTU
Power front left	19,000 BTU
Power front right	19,000 BTU
Total cooktop power	120,000 BTU
Cleaning	
Easy clean porcelain basepan	
Controls	
Metal illuminated dials	

FISHER & PAYKEL

QUICK REFERENCE GUIDE > CPV3-488-L

Power requirementsAmperage15ASupply frequency60HzSupply voltage120VProduct dimensions28"Depth28"Height8 5/16"Width47 7/8"	Simmer on all burners	140°F
Supply frequency 60Hz Supply voltage 120V Product dimensions 28" Height 8 5/16"	Power requirements	
Supply voltage 120V Product dimensions 28" Height 8 5/16"	Amperage	15A
Product dimensions Depth 28" Height 8 5/16"	Supply frequency	60Hz
Depth 28" Height 8 5/16"	Supply voltage	120V
Height 8 5/16"	Product dimensions	
-	Depth	28″
Width 47 7/8"	Height	8 5/16″
	Width	47 7/8″

Recommended Back Guards Ventilation

Combustible situation	BGCV2-3048H
Non combustible situation	BGCV2-3048 / BGCV2-1248
Pro hood	HCB48-12_N

Safety

ADA compliant

Warranty	
Parts and labor	2 years
SKU	82009

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

<u>+</u>	User Guide
<u> </u>	Service & Warranty
<u> </u>	Installation Guide
<u> </u>	Data Sheet Gas Rangetop and Low Backguard
<u> </u>	Data Sheet Gas Rangetop
<u> </u>	Data Sheet Gas Rangetop and Low Shelf High Backguard
<u> </u>	Data Sheet Gas Rangetop and High Shelf High Backguard

24/7

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com