QUICK REFERENCE GUIDE > RGV3-305-L

Gas Range, 30", 5 Burners, LPG

Series 7 | Professional

Stainless Steel | LPG



Professional style and performance, with high power burners delivering high heat or the most gentle simmer.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Convection oven with 4.6 cu ft total capacity
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from quality materials and real stainless steel

DIMENSIONS

Height	35 3/4 - 36 3/4"
Width	29 7/8"
Depth	29 1/8"

FEATURES & BENEFITS

COOKTOP POWER

Sealed Dual Flow Burners™ deliver cooktop power up to 17,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

COOKING FLEXIBILITY

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

DESIGN QUALITY

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, the Range is built to last.

EASY TO CLEAN

With a continuous, porcelain basepan, cleaning up spills is effortless. Your cooktop simply needs a quick wipe to keep it looking good as new.

TOTAL CONTROL

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Accessories (sold separately)

Square handle option AH-R30

Burner ratings	
Maximum burner power	17000 BTU
Power back left	11500BTU
Power back right	11500BTU 17000BTU 15000BTU 15000BTU
Power centre	
Power front left	
Power front right	
Total cooktop power	70000 BTU
Capacity	
Shelf positions	5
Total capacity	4.6cu ft
Usable capacity	3.4cu ft
Cleaning	
Easy clean porcelain basepan	•
Controls	
Electric circuit	3 wire
Metal illuminated dials	•
Gas Requirements	
Fitting and pipe	½ NPT min 5⁄7 ⅓ flex line

Fitting and pipe	½ NPT, min. ¾" 🛚 flex line
Supply Pressure (LPG)	11" to 14" W.C

Oven features

Auto re-ignition system

Electronic oven control

Broil pan	•

QUICK REFERENCE GUIDE > RGV3-305-L Date: 26.10.2023 > 2

Full extension telescopic	•
Infrared Broiler	
Internal light	
Titanium coated, illuminated	
Oven functions	
Bake	•
Broil	•
Convection bake	•
Number of functions	4
Slow cook	•
Oven performance	
Bake power	21,500 BTU
Broil power	19,000 BTU
Power requirements	
Amperage	15A
Rated current	15A
Supply frequency	60Hz
Product dimensions	
Depth	29 1/8"
Height	35 3/4 - 36 3/4"
Width	29 7/8"
Rangetop features	
Sealed range top	•
. 5	

Vent trim included

Recommended Back Guards Ventilation		
Combustible situation	BGRV3-3030H	
Non combustible situation	BGRV2-3030 / BGRV2-1230	
Recommended hood	HCB30-6_N (Professional	
Safety		
ADA compliant	•	
Full extension telescopic	•	
SKU	82007	

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



User Guide



Service & Warranty



Installation Guide

