Gas Range, 48", 5 Burners with Griddle

Series 7 | Professional

Stainless Steel | Natural gas



With Professional styling, this large range has five burners delivering powerful high heat, a griddle and two gas ovens.

- Griddle with burners that deliver up to 23,500 BTU heat per burner, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from guality materials and real stainless steel

DIMENSIONS

Height	35 3/4 - 36 3/4"
Width	47 7/8"
Depth	29 1/8″

FEATURES & BENEFITS

GENEROUS CAPACITY

Featuring a generous total capacity of 7.7 cu ft, with enough room to fit a 32 lb turkey. The griddle plate allows you to cook several foods at once.

COOKTOP POWER

Sealed Dual Flow Burners[™] deliver cooktop power up to 23,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

COOKING FLEXIBILITY

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

DESIGN QUALITY

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

EASY TO CLEAN

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

TOTAL CONTROL

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Accessories (sold separately)	
Square handle option	AH-R48
Burner ratings	
Maximum burner power	23500 BTU
Power back left	18500BTU
Power back right	18500BTU
Power centre	23500BTU
Power front left	18500BTU
Power front right	18500BTU
Power griddle	24000BTU
Total cooktop power	121500 BTU

Capacity

Shelf positions (main oven)	5
Shelf positions (second oven)	5
Total capacity (main oven)	5.3cu ft
Total capacity second oven	2.4cu ft
Usable capacity (main oven)	3.9cu ft

Cleaning

Easy clean porcelain basepan

Controls

Electric circuit 3 wire Metal illuminated dials

Gas Requirements

FISHER & PAYKEL

QUICK REFERENCE GUIDE > RGV3-485GD-N

Fitting and pipe	½ NPT, min. 5⁄8″ 🛛 flex line
Supply Pressure (natural gas)	6" to 9" W.C
Oven features	
Auto re-ignition system	•
Electronic oven control	•
Full extension telescopic	
Infrared Broiler	
Internal light	
Titanium coated, illuminated	
Oven functions	
Bake	
Broil	
Convection bake	
Slow cook	
Oven performance	
Main oven - Bake power	28,000 BTU
Main oven - Broil power	18,500 BTU
Secondary oven - Bake power	18,000 BTU
Power requirements	
Amperage	15A
Supply frequency	60Hz
Product dimensions	
Depth	29 1/8′
Height	35 3/4 - 36 3/4'

Width

Rangetop features Sealed range top Vent trim included

Recommended Back Guards Ventilation

Combustible situation	BGRV3-3048H
Non combustible situation	BGRV2-3048 / BGRV2-1248
Recommended hood	HCB48-12_N (48""

Safety

SKU

47 7/8"

Callety	
ADA compliant	•
Full extension telescopic	•
Secondary oven features	
3/4 Extension racks	2
Electronic oven control	•
Internal light	•
Secondary oven functions	
Bake	•

Convection bake	•
Number of secondary oven	4
Proof	•
Slow cook	•

81996

.

FISHER & PAYKEL

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020 Other product downloads available at fisherpaykel.com

- ✓ User Guide
- Service & Warranty
- ▲ Installation Guide



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com