

Integrated Warming Drawer, 30"

Series 9 | Integrated

Panel Ready



Keep plates warm until ready to serve; rapid proof or slow cook.

Panel-ready, you can match it with your cabinetry.

- Integrate your warming drawer into your surrounding cabinetry for seamless design
- Space to keep 16 standard-sized place settings evenly warm, with accessory rack for optimising space
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	10 11/16"
Width	28 7/16"
Depth	22 3/16"

FEATURES & BENEFITS

COMPLEMENTARY DESIGN

Our Warming Drawer is panel ready, blending seamlessly behind cabinetry with your choice of handle styles and custom door panel.

MULTI-FUNCTION FLEXIBILITY

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

EASY TO CLEAN

Cleaning and care of the Warming Drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

EASY TO USE

Soft-close with capacitive touch controls, our Warming Drawer comes with an accessory rack for optimising space.

PRECISE CONTROL

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

SAFE AND SOUND

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

SPECIFICATIONS

Accessories

Wire shelf	1
------------	---

Accessories (sold separately)

Handle kit Contemporary	Part 82105 (optional)
Handle kit Contemporary	Part 82103 (optional)
Handle kit Professional round	Part 82139 (optional)

Capacity

Accessory rack maximum	42lb
Cappuccino cups	24
Espresso cups	54
Maximum allowable weight	55lbs
Place settings	16
Usable depth	16 1/16"
Usable height	9 1/16"
Usable width	27 1/2"

Cleaning

Easy clean smooth-glass base	•
------------------------------	---

Controls

Audio feedback	•
Automatic timers	30', 45', 1h, 2h, 4h, 6h
Electronic capacitive touch	•
Pre-set heating functions	•
Sabbath mode	•
Soft close drawer	•
Standby mode	•

Functions

Cups	•
Dehydrate	•
Number of functions	6
Plates	•
Rapid proof	•
Slow cook	•
Warm	•

Performance

Heated glass base and fan	•
Low temperature cooking	•
Temperature levels	6
Temperature range	95°F-185°F

Power requirements

Amperage	10A
Power outlet	3-prong grounding-type
Supply frequency	60Hz
Supply voltage	110V

Product dimensions

Adjustable front door panel to	•
Depth	22 3/16"
Height	10 11/16"
Width	28 7/16"

Safety

Automatic turn off after 12	•
Full extension slides	•

Warranty

Parts and labor	2 years
-----------------	---------

SKU	82114
-----	-------

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- [↓](#) User Guide
- [↓](#) Service & Warranty
- [↓](#) Installation Guide
- [↓](#) Data Sheet Integrated Warming Drawer

**A PEACE OF MIND SALE****24 Hours 7 Days a Week Customer Support****T 1.888.936.7872 Wwww.fisherpaykel.com**