

#### IT-30RID





# **FEATURES**

Monitor and control remotely with Wi-Fi connectivity

Accepts custom panels for an integrated look within cabinetry or stainless-steel accessory panels and handles to match other Sub-Zero, Wolf, and Cove products

Preserves refrigerated foods with cool, moist air

Controls temperature within one degree of setpoint

Locks in cold air with a magnetic door seal system

Fight spoilage and odors with a NASA-inspired air purification system

Filters water, removing contaminants, chlorine taste, and odor

Delivers fresh, filtered water through an internal dispenser designed to discreetly rest within the refrigerator

Keeps produce fresher with high-humidity, sealed crisper and deli drawers

Refer to freshness cards for tips on food preservation, use, and care

Promotes easy clean-up with Nano-coated, spill-proof shelves

Control brightness with soft-on LED lighting

#### **ACCESSORIES**

Air Purification Cartridge

Egg Container

Reduced Toekick Divider

Stainless Steel Side Panel

Stainless Steel Top Panel

Water Filter

Stainless Steel Tubular Handles

Stainless Steel Pro Handles

**Dual Installation Kits** 

Stainless Steel Door Panels With Pro Handle

Stainless Steel Door Panels With Tubular Handle

Stainless Steel Drawer Panels With Pro Handles

Stainless Steel Drawer Panels With Tubular Handles

Stainless Steel Dual Installation Kickplates

Accessories are available through an authorized dealer. For local dealer information, visit <a href="mailto:subzero-wolf.com/locator">subzero-wolf.com/locator</a>.



**HANDLE ACCESSORIES** 



# **PRODUCT DETAILS**

# REFRIGERATOR

- · LED refrigerator lights
- · 4 glass refrigerator shelves (3 adjustable; 1 stationary)
- · Crisper drawer with dividers and sliding cover
- 1 deli drawer with adjustable dividers
- · 3 door bins (2 adjustable; 1 stationary)
- · 1 adjustable dairy compartment
- · Internal water dispenser



# **PRODUCT SPECIFICATIONS**

Model	IT-30RID
Dimensions	30"W x 84"H x 24"D
Door Clearance	28 1/2"
Drawer Clearance	18 3/8"
Weight	400 lbs
Refrigerator Capacity	16.5 cu. ft.
Electrical Supply	115 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Plumbing Supply	1/4" OD copper, braided stainless steel or PEX tubing
Plumbing Pressure	35–120 psi


### **ELECTRICAL**

# 

**FLOOR** 

1/4" (6)

### **PLUMBING**



PANEL SPECIFICATIONS For complete panels specifications including width/height, weight requirements and thickness requirements visit <a href="mailto:subzero-wolf.com/reveal">subzero-wolf.com/reveal</a>.


 $\textbf{NOTE:} \ \mathsf{Dimensions} \ \mathsf{in} \ \mathsf{parenthesis} \ \mathsf{are} \ \mathsf{in} \ \mathsf{millimeters} \ \mathsf{unless} \ \mathsf{otherwise} \ \mathsf{specified}$ 


# **INTERIOR VIEW**




This illustration is intended for interior reference only and may not represent the exterior of the model being specified.

# **DIMENSIONS**





## STANDARD INSTALLATION



NOTE: 31/2" (89) finished returns will be visible and should be finished to match cabinetry